

# Percept 0760BEE

---

LED EFFECT



---

**Percept** equips versatile  
interface that's brings lighting  
creation to next level.

---

## Range Technology Limited

✉ info@rangetech.com.hk

☎ +852 4614 8284

☎ +852 4614 8284

🏠 Flat /Rm509, 5/F, Yick Tai Industrial Building, 650 – 652 Castle Peak Road, Lai Chi Kok, Kowloon



# SPECIFICATIONS

## OPTIC

- Light source: 7\*60W Osram RGBW LEDs
- Life time: 50,000 Hours
- Color temperature: 2500-8000k adjustable

## MOVEMENT

- Extremely accurate positioning
- High-resolution stepper motors ensure extreme accuracy and smooth movements
- Auto-positioning, pan movement: 540° ( 16 bit ), tilt movement: 270° ( 16 bit )

## OTHER FUNCTION


- LED Over temperature protection
- Advanced cooling system, intelligent control of wind speed
- DMX Software update
- Show software version number
- Display LEDs and lanterns use time
- 100% brightness without stroboscopic problem
- Manual programming function
- Manual fine calibration function

## POWER SUPPLY

- Power consumption: 750W@220V
- AC 100~240V, 50/60Hz

## WEIGHT AND DIMENSION

- Net weight: 18KG
- Product size: ( see below )
- Carton size: 600\*400\*600MM
- Flight case size ( 2in1 ): 830\*480\*760MM



## COLORS

- Linear RGBW , color mixing with unlimited colors, dynamic colour macro effect with variable speed
- Super uniform light beam with no colour shadows

## EFFECT SECTION

- StRainbow, wash, beam, profile, effect modes ( kaleidoscope, swirl ), multiple macros
- Individual LED control for each parameter
- 3.5°-60° Electronic Zoom angle
- Front Lens Bi-directional continuous Rotation
- Digital Wash-Beam Framing effect
- Beam edge softening control ( in Wash mode )
- 0-100% linear electronic dimmer without color variation
- Adjustable speed stop/strobe effect with instantaneous blackout
- Dedicated channel for color temperature setting
- RGBW auto-tuning
- Control mode: International standard DMX512, 3-pin/5-pin DMX512
- Standard mode: 18/46 channels, Sound control mode, Stand-alone mode and standard mode: 25 channels
- Control mode: DMX512, 3-pin/5-pin DMX512; protocol RDM; wireless ( option ) and Art-Net ( option )
- Manual programming: DMX and RDM data IN/OUT
- Fan mode: NORMAL/PERFORMANCE/QUIET

## Range Technology Limited

✉ info@rangetech.com.hk

☎ +852 4614 8284

☎ +852 4614 8284


🏠 Flat /Rm509, 5/F, Yick Tai Industrial Building, 650 – 652 Castle Peak Road, Lai Chi Kok, Kowloon



# DMX CHANNEL

Channel NO.	Function	Description			
Ch1	Pan	000			255
Ch2	Pan Fine	000			255
Ch3	Tilt	000			255
Ch4	Tilt Fine	000			255
Ch5	R	000			255
Ch6	G	000			255
Ch7	B	000			255
Ch8	W	000			255
Ch9	Dimmer	000			255
Ch10	Shutter	000			255
Ch11	Color Temperature	000			255
Ch12	Color Macro	000			255
Ch13	Rotation	000			255
Ch14	Zoom	000			255
Ch15	Scan Speed	000	FAST		SLOW 255
Ch16	Dimmer Speed	000			255
Ch17	Dimmer Curve	000			255
Ch18	Control Fuction	000			255

LUMEN



## Range Technology Limited

info@rangetech.com.hk

+852 4614 8284

+852 4614 8284

Flat /Rm509, 5/F, Yick Tai Industrial Building, 650 – 652 Castle Peak Road, Lai Chi Kok, Kowloon

