Synapse Profile1000





Synapse equips with all essential components and precision, that bring all your creativity, the spark that you have in your mind to live.

Range Technology Limited

info@rangetech.com.hk
+852 4614 8284
+852 4614 8284

RANGE

🕼 Flat /Rm509, 5/F, Yick Tai Industrial Building, 650 – 652 Castle Peak Road, Lai Chi Kok, Kowloon

SPECIFICATIONS

ΟΡΤΙΟ

- Light Source: 1000W White LED Module
- Lumen: 40,000
- Life time: 50,000 Hours
- Color temperature: 6500K
- CRI: at least 70, CT 6500K
- CRI: at least 90, CT 5600K

MOVENMENT

- Pan movement: 540° (16 bit)
- Tilt movement : 270° (16 bit)
- Automatic reset function

COLORS

- Linear CMY+CTO
- Colors wheel: 1+5 colors

POWER SUPPLY


- Input voltage: AC 100V~240V 50/60Hz
- Rate power: 1360W@220V
- Power socket: power connector input and output
- DMX and RDM data IN/OUT : Locking 3pin & 5-pin XLR

IP GRADE


• IP: 20

WEIGHT AND DIMENSION

- Net weight: 34KG
- Product size: (see below)
- Carton size: 890*610*480MM
- Flight case size (1in1): 480*360*780MM



Range Technology Limited



- **(**+852 4614 8284
- +852 4614 8284

HOUSING

- Aluminum and steel structure with plastic covers
- Two side handles for transportation
- Device locking PAN and TILT mechanisms for transportation and maintenance
- Intellectual property rights of appearance and structure design
- Environmentally friendly flame retardant materials
- High temperature resistant engineering plastics

FEATURE

- Prism: 2pcs interchangeable, indexable prisms (4 facet prism+linear prism)
- Iris: Linear adjustable with macro
- Frost: Soft edge frost and flood frost
- Focus: DMX 512 linear focus
- Dimmer: 0-100% linear dimmer
- Strobe: Electronicstrobe, 0.3-20 TIMES/SEC
- Zoom: Smooth and fast speed
- Angle: 5°-55° linearadjustment
- Animation Wheel: 1 * interchangeable disc, clockwise and counter-clockwise rotation at variable speed

OTHER FUNCTION

- Show software version number Intelligent control of wind speed
- Display lamps and lanterns use time
- 100% brightness without stroboscopic problem
- Manual programming function
- Manual fine calibration function
- DMX and RDM data IN/OUT , Art-Net, wireless



DMX CHANNEL


Channel NO.	Function			Description		_	
Ch1	Pan	000	Ð	Ø		÷	255
Ch2	Pan Fine	000	Ð	i de la companya de l		æ	255
Ch3	Tilt	000					255
Ch4	Tilt Fine	000		盟			255
Ch5	Color Wheel	000		- 🔍 🕊 🖤 🕈	• •		255
Ch6	Cyan	000					255
Ch7	Magenta	000				_	255
Ch8	Yellow	000					255
Ch9	сто	000				-	255
Ch10	Fixed Gobo wheel	000	0	0000	••		255
Ch11	Rotating Gobo wheel	000	0		\mathbf{O}	9	255
Ch12	Gobos Auto-Rotation	000	0	(O)			255
Ch13	Dimmer	000		0		0	255
Ch14	Dimmer fine	000		0		0	255
Ch15	Strobe	000	0	1111	11	1 I	255
Ch16	Dimmer mode	000	DELAY	4	►	FAST	255
Ch17	Prism 1	000	\bigcirc	4	>	\circledast	255
Ch18	Prism 1 Rotation	000	\circledast	*			255
Ch19	Prism 2	000	0	4	→	\circledast	255
Ch20	Prism 2 Rotation	000	\circledast	*			255
Ch21	Zoom	000	Θ			⊕	255
Ch22	Zoom fine	000	Θ			⊕	255
Ch23	Focus	000	\$	4			255
Ch24	Focus fine	000	\$	4		A	255
Ch25	Iris	000	0			*	255
Ch26	Frost 1	000	٠	4	₽	٠	255
Ch27	Frost 2	000	٠	4	→	٠	255
Ch28	Animation wheel	000		4	→	٠	255
Ch29	Animation Rotation	000	٠	4	₽	٠	255
Ch30	Frame 1A	000	•	4		٠	255
Ch31	Frame 1B	000	٠	4	→	٠	255
Ch32	Frame 2A	000	٠	4	→	٠	255
Ch33	Frame 2B	000	٠	4	→	٠	255
Ch34	Frame 3A	000	٠	4		٠	255
Ch35	Frame 3B	000	•	4	→	٠	255
Ch36	Frame 4A	000	•	4	→	٠	255
Ch37	Frame 4B	000	•	4		٠	255
Ch38	Frame angle	000	٠	4	→	٠	255
Ch39	Frame marco	000	٠	4	→	٠	255
Ch40	Scan speed	000	FAST	4		SLOW	255
Ch41	Reset	000	•	4		٠	255

Range Technology Limited

info@rangetech.com.hk

- **(**+852 4614 8284
- 🕓 +852 4614 8284
- 🕼 Flat /Rm509, 5/F, Yick Tai Industrial Building, 650 652 Castle Peak Road, Lai Chi Kok, Kowloon





Intensity LUX(5°) (55°)



10

S